

USB232K

Product Specification

Specifications


Power Requirements Description	5 VDC at 30mA typical From USB RS232 to USB HID Keyboard USB Specification V 2.0 RS232,8N1,4800~38400 bpi
LED Indicator	Yellow LED: Link Green LED: TX Red LED: RX
Accessory System Requirement	WAS-1487 Win98II/2000/XP/VISTA
Dimensions Environment	L55.92xW35.0xH19.06mm Operating Temp : -10 ~ + 60 Deg.c Storage Temp : -20 ~ + 65 Deg.c Humidity : 10 ~ 90 relative



Pin Assignment

RS232	
Pin1	DCD
Pin2	RXD
Pin3	TXD
Pin4	DTR
Pin5	GND
Pin6	DSR
Pin7	RTS
Pin8	CTS
Pin9	RI

USB



Pin1	VCC
Pin2	D-
Pin3	D+
Pin4	GND

Dip Switch

DIP6	DIP7	DIP8	Language
OFF	ON	OFF	UK
ON	ON	OFF	FRANCE
OFF	OFF	ON	GERMANY
ON	OFF	ON	SPAIN
OFF	ON	ON	JPNAN
ON	ON	ON	ENGLISH

DIP2	DIP3	POWER
OFF	OFF	RI 5V
OFF	ON	DCD 5V

DIP4	DIP5	Baudrate
OFF	OFF	4800
OFF	ON	9600
ON	OFF	19200
ON	ON	38400

*Push "RESET" button after you make any setting.

Dimensions

