PROMAG[™]

PCR330 125KHz HID-Enabled Reader

Introduction:

PCR330 is a simple- to- use device applying 125Khz HID RFID technology to read the unique serial number of the RFID card. It is good to be used for the system access logon/logoff key and the system operator identification, such as POS system logon/logoff and operator identification /authorization with RFID card. PCR330 is a perfect system logon key, which can protect the system and prevent the unauthorized people from using the system.

Features:

- Plug & Play featuring. No driver required.
- Read 125KHz HID proximity cards
- Designed with USB interface
- Applies for system Logon/Logoff
- Access Control ID Registration

Specifications:

Power requirements	5 V / 200 mA
Interfaces	USB (keyboard emulation)
Card Type	HID Proximity card Wiegand 26, 34, 35, 37bits,
Card dimension	86 x 55 x 2 mm maximum
Dimension (mm)	W 65 X L 99.5 X D26 mm
Housing	ABS
Weight	115 g
Operating temperature	-10 ~ +55° C
Operating relative humidity	10 ~ 90 %

Ordering Information:

PCR330 : USB interface, 125KHz

% Specification is subject to change without notice.





We welcome OEM inquiries

Custom design manufacturing is

available

- Custom device programming is available
- Call factory for other configuration



8F.,NO.31, LANE 169, KANG-NING

STREET, HSI-CHIH, TAIPEI, TAIWAN

TEL: 886-2-26954214 FAX: 886-2-26954213 e-mail: promag@ms24.hinet.net promag@gigatms.com.tw http://www.gigatms.com.tw

PROMAGTM



PCR330 125KHz HID- Enabled Reader